



N120 0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2
FOR FULL FRAME 14MM EQUIVALENT LENSES TO 140° FULL ZOOM-THROUGH

	CAMERA LENS	GEAR	PORT ADAPTOR / EXTENSION RING	EXTENSION RING / PORT CONVERTER	PORT	OPTICAL PERFORMANCE
N120 NIKON SYSTEM EF & RF-Mount (RED CANON, PANASONIC, Z-CAM, BLACKMAGIC)	STANDARD ZOOM FULL FRAME	Canon RF 28-70mm f/2L USM	16343 RC2870Z RC2870Z	21140 / 22140 N120 Extension Ring 40 I / II	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 SN-AS26311 onwards	On Full Frame Sensor Lens FOV 75-63° Converted FOV 85-72° Zoom Range 28-35mm
	WIDE ANGLE APSC	Canon EF-S 10-18mm f/4.5-5.6 IS STM	16340 RC1018 Gear Set		85204 N120 WACP- 2	On APS-C Sensor Lens FOV 108-75° Converted FOV 128-85°
		Canon EF-S 10-22mm f/3.5-4.5 IS USM	16303 + 16304 RC1022-Z + RC1022-F	21110 N120 Extension Ring 10	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 before SN-AS26311	On APS-C Sensor Lens FOV 108-63° Converted FOV 128-72°
				22110 N120 Extension Ring 10 II	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 SN-AS26311 onwards	On APS-C Sensor Lens FOV 108-63° Converted FOV 128-72°
	WIDE ANGLE FULL FRAME	Tokina AT-X 11-20mm f/2.8 PRO DX	16328 RC1120 Gear Set	21120 / 22120 N120 Extension Ring 20 I / II	85204 N120 WACP- 2	On APS-C Sensor Lens FOV 100-68° Converted FOV 118-78°
		Canon RF 14-35mm f/4L IS USM	16342 CR1435 Gear Set	21110 N120 Extension Ring 10	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 before SN-AS26311	On APS-C Sensor Lens FOV 89-42° Converted FOV 104-48°
				22110 N120 Extension Ring 10 II	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 SN-AS26311 onwards	On Full Frame Sensor Lens FOV 114-63° Converted FOV 140-72°
		Canon RF 15-35mm f/2.8L IS USM	16341 CR1535 Gear Set	21135 / 22135 N120 Extension Ring 35 I / II	85204 N120 WACP- 2	On APS-C Sensor Lens FOV 84-42° Converted FOV 98-48°
		Canon RF 15-30mm f/4.5-6.3 IS STM	16345 CR1530 Gear Set		85204 N120 WACP- 2	On Full Frame Sensor Lens FOV 110-63° Converted FOV 133-72°
		Canon EF 16-35mm f/2.8 II USM	16311 + 16312 RC1635I-Z + RC1635II-F	21130 / 22130 N120 Extension Ring 30 I / II	85204 N120 WACP- 2	On APS-C Sensor Lens FOV 84-44° Converted FOV 98-51°
N120 NIKON Z-MOUNT (RED KOMODO-XV)	STANDARD ZOOM FULL FRAME	Nikkor Z 24-70mm f/2.8 S	19166 (V1) NZ2470-Z (V1)	21130 / 22130 N120 Extension Ring 30 I / II	85204 N120 WACP- 2	Lens FOV 84- 34° Converted FOV 98-40°
	WIDE ANGLE FULL FRAME	Nikkor Z 14-24mm f/2.8 S	19160 (V1) NZ1424-Z (V1)	21110 N120 Extension Ring 10	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 SN-AS26311 onwards	Lens FOV 114-87° Converted FOV 140-98°
				22110 N120 Extension Ring 10 II	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 SN-AS26311 onwards	Lens FOV 114-72° Converted FOV 140-81°
		Nikkor Z 14-30mm f/4 S	19156 (V1) NZ1430-Z (V1) or 19203 (V2) Z1430-Z (V2)		85204 N120 WACP- 2	Lens FOV 114-72° Converted FOV 140-81°
	WIDE ANGLE FX	Nikon AF-S NIKKOR 16-35mm f/4G ED VR	19138 N1635-Z	21150 / 22150 N120 Extension Ring 50 I / II	85204 N120 WACP- 2	Lens FOV 105-63° Converted FOV 128-72°
		Nikon AF-S 17-35mm f/2.8D IF-ED	19130 N1735-Z	21130 / 22130 N120 Extension Ring 30 I / II	85204 N120 WACP- 2	Lens FOV 104-63° Converted FOV 123-72°
	STANDARD ZOOM FX	Nikkor Z 24-70mm f/2.8 S II Lens	19236 (V3) Z2470H-Z (V3)	21155 / 22155 N120 Extension Ring 55 I / II	85204 N120 WACP- 2	Lens FOV 84- 34° Converted FOV 98-40°
			19236 (V3) + 19246 Z2470H-Z (V3) + Z2470H-FI	22225 N120 FTZ Adaptor ER 25 with Knob	21130 / 22130 N120 Extension Ring 30 I / II	
N120 NIKON Z-MOUNT (Z6II / Z8I / Z9I)	STANDARD ZOOM FX	Nikkor Z 14-24mm f/2.8 S	19160 (V1) NZ1424-Z (V1)	21110 N120 Extension Ring 10	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 before SN-AS26311	Lens FOV 114-87° Converted FOV 140-98°
	WIDE ANGLE FX	Nikkor Z 14-30mm f/4 S	19156 (V1) NZ1430-Z (V1) or 19203 (V2) Z1430-Z (V2)		85204 N120 WACP- 2	Lens FOV 114-72° Converted FOV 140-81°
		Nikkor Z 24-70mm f/2.8 S II Lens	19236 (V3) Z2470H-Z (V3)	21155 / 22155 N120 Extension Ring 55 I / II	85204 N120 WACP- 2	Lens FOV 84- 34° Converted FOV 98-40°
	WIDE ANGLE FX	Nikkor Z 14-24mm f/2.8 S	19234 (V3) Z1424-Z (V3)	21135 / 22135 N120 Extension Ring 35 I / II	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 before SN-AS26311	Lens FOV 114-87° Converted FOV 140-98°
					85204 N120 WACP- 2 * This setup is only compatible with WACP-2 SN-AS26311 onwards	Lens FOV 114-72° Converted FOV 140-81°
		Nikkor Z 14-30mm f/4 S	19235 (V3) Z1430-Z (V3)	22125 N120 Extension Ring 25 II	85204 N120 WACP- 2	Lens FOV 114-72° Converted FOV 140-81°
	STANDARD ZOOM FX	Nikkor Z 24-70mm f/2.8 S II Lens	19236 (V3) Z2470H-Z (V3)	21155 / 22155 N120 Extension Ring 55 I / II	85204 N120 WACP- 2	Lens FOV 84- 34° Converted FOV 98-40°
N120 CANON EF-MOUNT	STANDARD ZOOM FULL FRAME	Canon RF 28-70mm f/2L USM	19595 CR2870Z	21140 / 22140 N120 Extension Ring 40 I / II	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 SN-AS26311 onwards	Lens FOV 75-63° Converted FOV 85-72° Zoom Range 28-35mm
	WIDE ANGLE APSC	Canon RF 14-35mm f/4L IS USM	19574 CR1435-Z	21110 N120 Extension Ring 10	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 before SN-AS26311	Lens FOV 114-63° Converted FOV 140-72°
				22110 N120 Extension Ring 10 II	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 SN-AS26311 onwards	Lens FOV 110-71° Converted FOV 133-81°
		Canon RF 15-30mm f/4.5-6.3 IS STM	19597 CR1530-Z		85204 N120 WACP- 2	Lens FOV 110-63° Converted FOV 133-72°
	WIDE ANGLE FULL FRAME	Canon RF 16-35mm f/2.8 II USM	19554 C16350-Z	21150 / 22150 N120 Extension Ring 50 I / II	85204 N120 WACP- 2	Lens FOV 107-63° Converted FOV 128-72°
		Canon RF 16-35mm f/4 IS USM	19548 C16354-Z	21130 / 22130 N120 Extension Ring 30 I / II	85204 N120 WACP- 2	Lens FOV 108-63° Converted FOV 128-72°
	STANDARD ZOOM FULL FRAME	Canon RF 28-70mm f/2L USM	19595 CR2870Z	21140 / 22140 N120 Extension Ring 40 I / II	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 SN-AS26311 onwards	Lens FOV 75-63° Converted FOV 85-72° Zoom Range 28-35mm
N120 CANON RF-MOUNT (C50 / R5II)	STANDARD ZOOM FULL FRAME	Canon RF 14mm f/1.4 L VCM	19632 RF1435-Z	21125 / 22125 N120 Extension Ring 25 I / II	85204 N120 WACP- 2	Lens FOV 114° Converted FOV 140°
	WIDE ANGLE FULL FRAME	Canon RF 14-35mm f/4L IS USM	19632 RF1435-Z	21130 / 22130 N120 Extension Ring 30 I / II	85204 N120 WACP- 2	Lens FOV 114-63° Converted FOV 140-72°
		Canon RF 15-35mm f/2.8L IS USM	19631 + 19643 RF1535-F RF1535-F * Focus gear (19643) is compatible with C50 only	21155 / 22155 N120 Extension Ring 55 I / II	85204 N120 WACP- 2	Lens FOV 110-63° Converted FOV 133-72°
	WIDE ANGLE FULL FRAME	Panasonic Lumix S PRO 16-35mm f/4	19728 PL1635-Z		85204 N120 WACP- 2	Lens FOV 105-63° Converted FOV 128-72°
		Sigma 14-24mm f/2.8 DG DN Art	19726 SLE1424-Z	21125 / 22125 N120 Extension Ring 25 I / II	85204 N120 WACP- 2	Lens FOV 105-63° Converted FOV 128-72° Zoom Range 20-24mm
	MACRO MEDIUM FORMAT	Laowa 17mm f/4 GFX Zero-D	19824 + 19825 GL17A + GL17F	21135 + 22151 / 22135 + 22151 N120 Extension Ring 35 I + Focus Knob / N120 Extension Ring 35 II + Focus Knob	85204 N120 WACP- 2	Lens FOV 114° Converted FOV 140°
		Fujifilm GF 20-35mm F4 R WR	19827 GF2035-Z	21135 / 22135 N120 Extension Ring 35 I / II	85204 N120 WACP- 2	Lens FOV 108-76° Converted FOV 132-93°
		Fujifilm GF 23mm F4 R LM WR		21120 / 22120 N120 Extension Ring 20 I / II	85204 N120 WACP- 2	Lens FOV 100° Converted FOV 118°
N120 FUJIFILM GF-MOUNT	STANDARD ZOOM FULL FRAME	Canon EF 16-35mm f/2.8 II USM with Metabones EF-GFX mount Smart Expander 1.26x	TBD COF1635H-Z	21180 / 22180 N120 Extension Ring 80 I / II	85204 N120 WACP- 2	Lens FOV 107-63° Converted FOV 128-72°
	WIDE ANGLE FULL FRAME	Canon EF 16-35mm f/4 IS USM with Metabones EF-GFX mount Smart Expander 1.26x	TBD COF1635H-Z	21160 / 22160 N120 Extension Ring 60 I / II	85204 N120 WACP- 2	Lens FOV 107-63° Converted FOV 128-72°
	STANDARD ZOOM FULL FRAME	Sony FE 20-70mm f/4 G	37174 SFE2070-Z	37305 N100 to N120 35.5mm Port Adaptor II	85204 N120 WACP- 2 * slight vignetting at 20mm in RAW format	Lens FOV 94-59° Converted FOV 116-73° Zoom Range 20-38mm
		Sony SEL2470GM FE 24-70mm f/2.8 GM	37151 SFE2470GM-Z	37305 N100 to N120 35.5mm Port Adaptor II	21130 / 22130 N120 Extension Ring 30 I / II	85204 N120 WACP- 2
			37151 + 37152 SFE2470GM-Z + SFE2470GM-F	* This setup is only compatible with 37305 SN-A544975 onwards, older version 37305 can be upgraded using lock mechanism 95851		Lens FOV 84-34° Converted FOV 98-74° Zoom Range 24-35mm
	WIDE ANGLE FULL FRAME	Sigma 24-70mm f/2.8 DG DN Art	37171 SSF2470-Z	37305 N100 to N120 35.5mm Port Adaptor II	21120 / 22120 N120 Extension Ring 20 I / II	85204 N120 WACP- 2
				* This setup is only compatible with 37305 SN-A544975 onwards, older version 37305 can be upgraded using lock mechanism 95851		Lens FOV 84-64° Converted FOV 98-74° Zoom Range 24-34mm
N100 SONY E-MOUNT	STANDARD ZOOM FULL FRAME	Sony FE 14mm f/1.8 GM	37145 + 37146 SE1635-Z + SE1635-F	37305 N100 to N120 35.5mm Port Adaptor II	21110 N120 Extension Ring 10	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 before SN-AS26311
	WIDE ANGLE FULL FRAME	Sony SEL1635OM FE 16-35mm f/2.8 OM	37155 SFE1635OM-Z	37305 N100 to N120 35.5mm Port Adaptor II	21130 / 22130 N120 Extension Ring 30 I / II	85204 N120 WACP- 2
			37155 + 37156 SFE1635OM-Z + SFE1635OM-F	* This setup is only compatible with 37305 SN-A544975 onwards, older version 37305 can be upgraded using lock mechanism 95851		Lens FOV 107-63° Converted FOV 128-72°
		Sony SEL1635OM2 FE 16-35mm f/2.8 GM II	37175 SFE1635OM2-Z	37305 N100 to N120 35.5mm Port Adaptor II	21110 N120 Extension Ring 10	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 before SN-AS26311
	WIDE ANGLE FULL FRAME	Sony SEL1635Z Vario-Tessar T* FE 16-35mm F4 ZA OSS	37145 + 37146 SE1635-Z + SE1635-F	37305 N100 to N120 35.5mm Port Adaptor II	21110 N120 Extension Ring 10	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 before SN-AS26311
				* This setup is only compatible with 37305 SN-A544975 onwards, older version 37305 can be upgraded using lock mechanism 95851	22110 N120 Extension Ring 10 II	85204 N120 WACP- 2 * This setup is only compatible with WACP-2 SN-AS26311 onwards
	STANDARD ZOOM FULL FRAME	Sony FE PZ 16-35mm f/4 G	37172 SFE1635-Z	37306 N100 to N120 25mm Port Adaptor		85204 N120 WACP- 2
						Lens FOV 107-63° Converted FOV 128-77°
	WIDE ANGLE FULL FRAME	Sony FE 24mm f/1.4 GM		37305 N100 to N120 35.5mm Port Adaptor II		85204 N120 WACP- 2
				* This setup is only compatible with 37305 SN-A544975 onwards, older version 37305 can be upgraded using lock mechanism 95851		Lens FOV 84° Converted FOV 98°
		Sigma 14-24mm f/2.8 DG DN	19728 SLE1424-Z	37305 N100 to N120 35.5mm Port Adaptor II	21125 / 22125 N120 Extension Ring 25 I / II	85204 N120 WACP- 2

85204

N120 0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2 (WACP-2)
For Full Frame 14mm Equivalent Lenses to 140° Full Zoom-Through

Specifications

Dimension (mm)	:	DIA 297 x H 220 (from port mount to front lens element)
Weight in Air	:	7.35 kg
Buoyancy in Water	:	Negative 0.27 kg
Body Construction	:	Hard-anodized aluminum alloy
Lens Construction	:	4 Elements
Lens Coating	:	Anti-corrosion coating outside of dome
Focus Distance	:	From front element of lens to infinity
Maximum FOV (underwater)	:	140° (Ref. 28mm equivalent)
Lens Mount	:	N120 Port Mount
Depth Rating	:	100m
Pre-installed	:	Integrated aluminium float collar

Package includes

- WACP-2
- Front hard lens cap
- Rear lens caps
- Padded carrying bag
- 90140 N120 Port O-ring
- Cleaning Cloth
- Lubricant

Last Updated : 2026-05-21

* This port chart is subject to updating as new information becomes available